

MERITOR® AUTOMATIC SLACK ADJUSTER



MERITOR

Proven to Go the Extra Mile

As the leading supplier of automatic slack adjusters (ASA) in North America, Meritor understands the delicate relationship between ASAs and foundation brakes. The Meritor ASA, designed for a variety of commercial vehicle applications, has been proven over billions of service miles.

Performance advantages:

- Maximum reliability and robustness
- Lowest cost and lightest weight ASA on the market
- Only ASA that adjusts on chamber stroke
- 25,000 in-lbs. torque capacity
- Pawl design simplifies service



Automatic Slack Adjuster


**LIGHTEST
WEIGHT**
AVAILABLE

 **25 THOUSAND
POUNDS**
TORQUE CAPACITY

 **EASY
TO SERVICE**



Meritor Automatic Slack Adjuster

Meritor's unique design keeps brakes in constant adjustment while eliminating the need for frequent under-the-truck brake adjustments. This reduces brake maintenance costs and vehicle safety inspection citations while also optimizing brake performance.

Features and Benefits

- Pull pawl design requires fewer moving parts, enhancing durability and reliability
- Stroke sensing design
- Keeps brakes properly adjusted for shorter stopping distances and longer lining life
- Fully sealed to resist internal contamination for longer life
- Industry's lightest weight ASA, which increases payload and camshaft bracket life
- Grease purge to camshaft resists binding
- Ratchet type adjuster minimizes internal wear which results in robust design and maximizes reliability
- Self-contained design doesn't require special grounding straps, simplifies installations
- Simple to manually adjust with no anti-reverse springs to overcome



Unmatched Customer Support

Every Meritor ASA is backed by unsurpassed service and support, with Meritor DriveForce™ – Meritor's North American sales and service organization – and the OnTrac™ technical support center available to assist customers with solutions before, during and after the sale. For more information, call 866-668-7221 or visit meritor.com today.

Automatic Slack Adjuster Specifications

Specifications	Front Steer Axle	Drive and Trailer Axle
Slack Length (inches)	5.0, 5.5	5.0, 5.5, 6.0, 6.5, 7.0
Arm Configuration	Straight 0.625" offset clevis	
Camshaft Spline Size and No.	1.25 - 24 1.25 - 10 1.50 - 10 1.50 - 28	1.50 - 10 1.50 - 28 1.625 - 37
Clevis Thread	.50" - 20 for chamber type 9,12,16 .625" - 18 for 20, and larger chambers	.625"-18 for type 20,24,30,36 chambers



Meritor Heavy Vehicle Systems, LLC
2135 West Maple Road
Troy, Michigan 48084 USA

Call 1-866-668-7221
or visit meritor.com.

©2015 Meritor, Inc.
Litho in USA
Revised 6-15
SP-0737