

GEHL

SKID LOADERS



GEHL[®]
WORKS LIKE YOU[™]



**BORN ON AN
AMERICAN FARM
IN 1859.**

GEHL[®]

WORKS LIKE YOU[™]

Starting in 1859 GEHL has been rooted in agriculture. Designing and building machines to help America's hardest workers. Many years later, we are offering products world-wide that work just as hard as the people who own and operate them.

We build machines that make life easier and exceed expectations. Here at GEHL we know that true satisfaction isn't felt while earth-moving but looking back at a job well-done. That is the true payoff for our operators and built in our DNA at GEHL.

For over 160 years we have been partnering with farmers, construction crews, landscapers and rental companies – large and small – to help move mountains and build a strong foundation of trust. **We care about our operators.** Safety and efficiency go into every machine we produce to help hardworking people get home safe and maybe even a little bit early. ■

The true payoff comes in a job well-done.

**RAISED ON
A GLOBAL
JOB SITE.**

GEHL

We have always designed and built machines to help the needs of the people who change our landscape. Over time, regulations and the needs of these workers change. GEHL continues to innovate and change with them to supply the most robust durable machines on the market.

Humble and hard working people, responsible for molding and changing the world around us are not overlooked by our brand. With that in mind, GEHL has contributed heavily to the construction industry and is dedicated to continue for many years to come.

GEHL has invested significantly into the future of our products and will continue to change and meet the requirements of urban job sites. Driven by the voice of our customers and industry data we are committed to be here to design, build, service and stand behind our products. We will help you do the heavy lifting.

As the global landscape changes we stay on track supplying machines that are reliable and meet or exceed emissions standards for the future of our planet and our young operators of tomorrow. ■

SKID LOADERS



R105

Height to Hinge Pin-Fully Raised
- 108" | 2743mm
Rated Operating Capacity
- 1,050lbs | 476kg
Operating Weight
- 4,200 lbs | 1905kg

RADIAL LIFT

Ultra Compact
H - 71" / W - 47" / L - 91"
Perfect Rental Machine
Easy to Transport



R135

Height to Hinge Pin-Fully Raised
- 110" | 2794mm
Rated Operating Capacity
- 1,350lbs | 612kg
Operating Weight
- 5,255 lbs | 2384kg

RADIAL LIFT

Compact
H - 75" / W - 55" / L - 91"
Pilot Joystick Controls
Great for Rental
Easy to Transport



R165

Height to Hinge Pin-Fully Raised
- 118.5" | 3018mm
Rated Operating Capacity
- 1,650lbs | 748kg
Operating Weight
- 6,164 lbs | 2796kg

RADIAL LIFT

Compact
H - 77" / W - 63" / L - 94"
Optional Pilot Joystick Controls
Wicked Speed
Operator Favorite



R190^{GEN-2}

Height to Hinge Pin-Fully Raised
- 119" | 3023mm
Rated Operating Capacity
- 1,900lbs | 862kg
Operating Weight
- 6,995 lbs | 3173kg

RADIAL LIFT

Compact
H - 75" / W - 63" / L - 94"
Largest Radial Lift Loader
Powerful Lifting
Operator Must-Have



V210

Height to Hinge Pin-Fully Raised
- 120.5" | 3061mm
Rated Operating Capacity at 50%
- 2,100lbs | 952kg
Operating Weight
- 7,480 lbs | 3393kg

VERTICAL LIFT

Mid-Size Loader
H - 79" / W - 63" / L - 138"
Pilot Joystick Controls
Expanded Lift Height



V230

Height to Hinge Pin-Fully Raised
- 121.5" | 3086mm
Rated Operating Capacity at 50%
- 2,300lbs | 1043kg
Operating Weight
- 7,710 lbs | 3497kg

VERTICAL LIFT

Mid-Size Loader
H - 79" / W - 67" / L - 142"
Great for Construction
Manufacturer's Favorite



V275

Height to Hinge Pin-Fully Raised
- 129" | 3277mm
Rated Operating Capacity
- 2,750lbs | 1247kg
Operating Weight
- 8,320 lbs | 3774kg

VERTICAL LIFT

Mid-Size Loader
H - 81.5" / W - 67" / L - 150"
Joystick Controls Standard
Powerful Design



NEW! V325

Height to Hinge Pin-Fully Raised
- 134.2" | 3409mm
Rated Operating Capacity
- 3,250lbs | 1474kg
Operating Weight
- 9,100 lbs | 4128kg

VERTICAL LIFT

Large Loader
H - 82" / W - 72.9" / L - 123"
Load Sensing Hydraulics
Yanmar Engine



NEW! V335

Height to Hinge Pin-Fully Raised
- 131" | 3409mm
Rated Operating Capacity
- 3,350lbs | 1520kg
Operating Weight
- 9,835 lbs | 4461kg

VERTICAL LIFT

Large Loader
H - 82" / W - 72.9" / L - 123"
Deutz Engine
Load Sensing Hydraulics



NEW! V360

Height to Hinge Pin-Fully Raised
- 131" | 3454mm
Rated Operating Capacity
- 3,600lbs | 1633kg
Operating Weight
- 10,320 lbs | 4681kg

VERTICAL LIFT

Large Loader
H - 84" / W - 75.4" / L - 124.9"
Load Sensing Hydraulics
Highest Dumping Height

KEEPING YOU ROLLIN'

VISIBILITY

Excellent sightlines from all sides for safe and precise placement of loads and reduced jobsite incidents. A high-mounted seat provides an excellent vantage point to the attachment and cutting-edge.

NEW! SLOPED ROOF

Our newly designed roof minimizes the front, upper cross section to improve your visibility. With the roof pitched in the middle, it directs rainfall and other debris to your outer edges, keeping your eyes on the attachment and job at hand.

Available on V210, V230, V275, V325, V335 and V360 only

CLIMATE CONTROL

Upgrade to Pressurized Cab Enclosure with air conditioning and heat to utilize the most of your machine. No matter the weather, you'll be running comfortably. Optional air ride seat and Bluetooth radio are two additions that help any operator with long hours of operation.

SAFETY

Our heavy duty doors offer operator protection, easy entry/exit and are well sealed for maximum operator climate controlled comfort. Add AC/Heat and you'll feel the difference and never go back.

NEW MODELS V325 | V335 | V360

- 23% More Cab Volume
- Over 20% Increased Visibility
- Easy Entrance Lowered 3"
- Increased Ground Speeds
- Re-Imagined Serviceability

NEW! SLOPED LIFT ARMS

New design to give a better view to your surroundings. It also limits the material build up on top of arms, while keeping your hydraulic lines protected.

Available on V210, V230, V275, V325, V335 and V360 only

MAINTENANCE

Excellent service access and quality components pair up to provide durable machines that are easy to maintain.

IdealAccess® - INDUSTRY EXCLUSIVE

A proprietary feature of the Pilot Series skid loaders is the IdealAccess® fold-up door. The optional fold-up door design provides an overall machine operating height that is several inches lower than machines with over-head door systems. It's unique in the fact that it folds up and everything stays in front of the operator, providing more overhead room free of obstructions. Available on V210, V230, V275, V325, V335 and V360

NEW! HYDRAULIC LOAD SENSING

Improve your efficiency with our new hydraulic load sensing. Reduce fuel consumption and boosts performance by powering the functions at correct levels.

Available on V325, V335 and V360 only

REAR BUMPER

The rear bumper protects the rear of the machine from accidental damage and increases the rated operating capacity.*

**Increases capacity on V210, V230, V275, V326 and V330*

SERVICE

Easy access to the chain case makes maintenance and repairs much faster getting you back on the job site or in the fields with minimal down time to your machine. Greasable pins make daily maintenance a breeze.*

**V210, V230, V275, V325, V335 and V360 only*

ATTACHMENTS

A full line of attachments and accessories are designed specifically to fill operators' needs, making their GEHL the most versatile machine on the job site. Some popular attachments that transform your machines in minutes are: Augers, Backhoes, Bale Clamps/Spars, Brooms, Mowers, High Dump Buckets, Grapples, and Pallet Forks. Upgrade to hydraulic Power-A-Tach® to change and secure new attachments without leaving the comfort of your cab.



LET'S GET INSIDE

WE UNDERSTAND THE CAB IS YOUR OFFICE.

We offer many standard and optional features to improve operator comfort and know the importance of being comfortable while working. Not only for operator fatigue but also for overall job site safety and employee retention. A comfortable and alert operator is a safe operator. Please consider these well-thought-out features and the benefits your crew will have when building your next loader.

PRESSURIZED CAB

An optional pressurized, sealed cab enclosure provides a cleaner, quieter operating environment.

INTERIOR LIGHTS

We know our operators start at dawn and work past dusk, so we have interior lights and optional additional work lights to fit your needs.

EXCELLENT VIEWS FROM ALL SIDES

Safe, clear visibility for precise operation. Rear window is removable for alternative exit in emergencies.

OVER 20% INCREASED VISIBILITY on V210, V230, V275, V325, V335 + V360

POWER PORT

12-volt accessory plug keeps your devices fully charged. USB Port also available on V210, V230, V275, V325, V335 + V360.



2" (51 MM) SEATBELT

Optional 3" (76 mm) seatbelt available.

CONTROL OPTIONS

Hand/Foot, T-Bar, Dual-hand or Joystick available on selected models.*

*Not available on all models



DUAL-HAND



T-BAR



HAND/FOOT



JOYSTICK

ADJUSTABLE CONTROLS

Controls extend and retract to provide personalized comfort.

SPACIOUS COMFORT

Keeping you comfortable after a long day and some models have easy removable foot plate or easy cleaning of the cabin floor.

23% LARGER CABS on V210, V230, V275, V325, V335 + V360



BEST IN CLASS - STANDARD ROPS II OVERHEAD PROTECTION

Standard on R105, R135, R165 and R190.
Optional on V210, V230, V275, V325, V335 and V360.

MULTIPLE AIR VENTS

Adjustable vents throughout the cab provide optimal temperature control.

HEAVY-DUTY SIDE PROTECTION

Sliding windows open for venting and communicating while still protected by single piece metal guarding.

EASY ENTRY AND EXIT

Large entry area allows for easy access to the operator station.

BLUETOOTH MP3 RADIO

Optional upgrade to wirelessly play music or podcasts using the speakers in the cab.

ADJUSTABLE SEAT

Choose between an air-ride suspension or mechanical suspension seat.

NEW BRANDED, CLOTH SEAT available on V210, V230, V275, V325, V335 + V360

PADDED, ADJUSTABLE ARMRESTS

OPERATOR SAFETY

The machine safety system (Hydraloc™) allows operation only when the user is on the seat and the restraint bar is lowered into position.

CUP HOLDER

CLIMATE CONTROL

Heat is standard on all cab models. Air conditioning is an option on select models.

STORAGE COMPARTMENTS

Designed for your phone, keys and other items you need within arms reach.

VISIBILITY + SAFETY

Every machine we manufacture is inspired by safety—from a more comfortable cab that reduces operator fatigue to a pressure-sensitive seat that only works when a user sits with the restraint bar lowered. Clear visibility from all sides of the machine allow for precision operation that raises productivity and minimizes accidents. We also designed our Skid Loaders with heavy-duty

doors and the highest level of safety protection for an operator in a roll over or falling object situation with industry leading Level II Falling Object Protective Structure (FOPS) and Roll-Over Protective Structure (ROPS)*. At the end of the day, nothing is more important than ensuring you get home safe after leaving the jobsite.

**Optional Feature on R135, R165, V210, V230 and V275*

VERTICAL OR RADIAL?

Depending on your needs and situation, we offer both radial lift and vertical lift Skid Loaders. Our radial lift loaders offer extended reach at the middle of the lift path and are designed for easier, more accessible on-site serviceability. Our

vertical lift loaders provide more reach at full lift height, making them optimal for applications that require loading and stacking at high heights. Plus, you can increase the lift capacity of a vertical lift loader by keeping the load closer to the machine.

ADDITIONAL FEATURES ON OUR V210, V230, V275, V325 V335 +V360 MODELS

REAR VIEW CAMERA



This optional feature improves visibility and increases the safety of those around you while operating.

LARGER CABS

Cabin space has been increased by 23% allowing you to be even more comfortable all day long.

NEW DIGITAL DISPLAY




Check fuel consumption, engine RPM's, machine hours, engine diagnostic codes, warning indicators and much more. Additionally, you can now start your engine with keyless entry.

EASY ENTRANCE

The entrance of our cabs have been lowered 3", allowing you more space for efficient entry and exit.

KEEP YOUR PROJECT ROLLING

Skid loaders are usually the first of the machines to show up at a new build. The perfect machine for earthmoving, land prep and concrete flatwork. Get behind the controls of a GEHL skid loader at your local dealer and you'll feel the difference.



Scan with your phone to find your local dealer.

www.gehl.com/en-US/store-locator

SMALL FRAME SKID LOADERS



R105

Capacities	
Rated Operating Capacity	1,050 lb (476 kg)
Rated Operating Capacity w/ Counterweight	1,175 lb (533 kg)
Unladen weight	3,700 lb (1678 kg)
Weight and Dimensions	
Overall Operating Height - Fully Raised	142" (3607 mm)
Height to Hinge Pin - Fully Raised	108" (2731 mm)
Overall Height to Top of ROPS	70" (1784 mm)
Dump angle at full height	40°
Dump height	82" (2083 mm)
Overall length with bucket	118" (2997 mm)
Dump reach - Full height	25" (641 mm)
Rollback at ground	31°
Seat to ground height	33" (826 mm)
Wheelbase	34" (876 mm)
Overall width less bucket	48" (1224 mm)
Bucket Width	54" (1372 mm)
Ground clearance	6" (159 mm)
Overall length - Less Bucket	89" (2248 mm)
Clearance Radius - Front with Bucket	72" (1829 mm)
Clearance Circle - Front without Bucket	42" (1067 mm)
Clearance Circle - Rear	54" (1372 mm)
Performances	
Travel speed (unladen)	5 mph (8.26 km/h)
Wheels	
Standard tires	27x8.5x15 HD
Engine	
Engine brand	Yanmar
Engine model	3TNV88C-KMSV Stage V
Engine norm	Stage IV / Tier 4 Final
Gross Power (kW)	34.2 hp (25.2 kW)
Max. torque / Engine rotation	81 ft-lbs / 1820 rpm
Battery	12 V
Starter (kW)	2.3 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	15 gpm (55 l/min)
Tank Capacities	
Fuel tank	9.5 gal (36 l)
Reservoir Capacity Hydraulics	8 gal (30.30 l)
Noise and Vibration	
Environmental noise (LwA)	101 dB
Whole-Body Vibration (ISO 2631-1)	1.12 m/s ²
Vibration to whole hand/arm	< 1.70 m/s ²

R135

Capacities	
Rated Operating Capacity	1,350 lb (612 kg)
Rated Operating Capacity w/ Counterweight	1,499 lb (680 kg)
Unladen weight	4,765 lb (2161 kg)
Weight and Dimensions	
Overall Operating Height - Fully Raised	144" (3670 mm)
Height to Hinge Pin - Fully Raised	110" (2790 mm)
Overall Height to Top of ROPS	76" (1930 mm)
Dump angle at full height	40°
Dump height	84" (2123 mm)
Overall length with bucket	121" (3073 mm)
Dump reach - Full height	23" (591 mm)
Rollback at ground	28°
Seat to ground height	34" (871 mm)
Wheelbase	37" (950 mm)
Overall width less bucket	54" (1372 mm)
Bucket Width	54" (1372 mm)
Ground clearance	8" (201 mm)
Overall length - Less Bucket	93" (2360 mm)
Clearance Radius - Front with Bucket	73" (1842 mm)
Clearance Circle - Front without Bucket	44" (1120 mm)
Clearance Circle - Rear	54" (1372 mm)
Performances	
Travel speed (unladen)	8 mph (12.90 km/h)
Wheels	
Standard tires	10.00x16.5 HD
Engine	
Engine brand	Yanmar
Engine model	4TNV88C
Engine norm	Stage IV / Tier 4 Final
Gross Power (kW)	46 hp (34 kW)
Max. torque / Engine rotation	108 ft-lbs / 1820 rpm
Battery	12 V
Starter (kW)	2.3 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	17 gpm (63.60 l/min)
Tank Capacities	
Fuel tank	16 gal (59.40 l)
Reservoir Capacity Hydraulics	9.2 gal (39.8 l)
Noise and Vibration	
Environmental noise (LwA)	101 dB
Whole-Body Vibration (ISO 2631-1)	0.81 m/s ²
Vibration to whole hand/arm	< 1.77 m/s ²

R165

Capacities	
Rated Operating Capacity	1,650 lb (748 kg)
Rated Operating Capacity w/ Counterweight	1,800 lb (816.50 kg)
Unladen weight	5,575 lb (2527 kg)
Weight and Dimensions	
Overall Operating Height - Fully Raised	153" (3876 mm)
Height to Hinge Pin - Fully Raised	119" (3018 mm)
Overall Height to Top of ROPS	77" (1956 mm)
Dump angle at full height	38°
Dump height	94" (2380 mm)
Overall length with bucket	122" (3101 mm)
Dump reach - Full height	23" (579 mm)
Rollback at ground	28°
Seat to ground height	36" (904 mm)
Wheelbase	39" (986 mm)
Overall width less bucket	62" (1580 mm)
Bucket Width	61" (1562 mm)
Ground clearance	6" (160 mm)
Overall length - Less Bucket	94" (2385 mm)
Clearance Radius - Front with Bucket	74" (1869 mm)
Clearance Circle - Front without Bucket	45" (1153 mm)
Clearance Circle - Rear	58" (1466 mm)
Performances	
Travel Speed with Two-Speed - Maximum	12 mph (19.50 km/h)
Wheels	
Standard tires	10.00x16.5 HD
Engine	
Engine brand	Yanmar
Engine model	4TNV98C-NMS2V
Engine norm	Stage IV / Tier 4 Final
Gross Power (kW)	69.3 hp (51.7 kW)
Max. torque / Engine rotation	178 ft-lbs / 1625 rpm
Battery	12 V
Starter (kW)	3 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	20 gpm (77 l/min)
High-Flow Auxiliary Hydraulics - Option	30 gpm (114 l/min)
Tank Capacities	
Fuel tank	17 gal (62.50 l)
Reservoir Capacity Hydraulics	10 gal (39 l)
Noise and Vibration	
Environmental noise (LwA)	101 dB
Whole-Body Vibration (ISO 2631-1)	1.05 m/s ²
Vibration to whole hand/arm	< 1.53 m/s ²

R190

Capacities	
Operating Capacity At 50% Tipping Load	1,900 lb (862 kg)
Operating Weight	6,995 lb (3173 kg)
Unladen Weight	6,510 lb (2953 kg)
Weight and Dimensions	
Overall Operating Height - Fully Raised	157" (3993 mm)
Height to Hinge Pin - Fully Raised	119" (3023 mm)
Overall Height to top of ROPS	77" (1956 mm)
Dump angle at full height	39°
Dump height	91" (2313 mm)
Overall length with bucket	128" (3261 mm)
Dump reach - Full height	26.3" (667 mm)
Rollback at ground	28°
Seat to ground height	36" (904 mm)
Wheelbase	42" (1067 mm)
Overall width less bucket	62" (1575 mm)
Bucket Width	66" (1676 mm)
Ground clearance	6" (160 mm)
Overall length - Less Bucket	96" (2446 mm)
Clearance Radius - Front with Bucket	80" (2032 mm)
Clearance Circle - Front without Bucket	46" (1168 mm)
Clearance Circle - Rear	59" (1511 mm)
Performances	
Travel Speed with Two-Speed - Maximum	12 mph (19.47 km/h)
Wheels	
Standard tires	10 x 16.5
Engine	
Engine brand	Yanmar
Engine model	4TNV98C-NMS2V
Engine norm	Stage IV / Tier 4 Final
Gross Power (kW)	69.3 hp (51.7 kW)
Max. torque / Engine rotation	178 ft-lbs / 1625 rpm
Battery voltage	12 V
Starter (kW)	3 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	20 gpm (70.78 l/min)
High-Flow Auxiliary Hydraulics	30 gpm (114 l/min)
Tank Capacities	
Fuel tank	16 gal (58.67 l)
Reservoir Capacity Hydraulics	9 gal (35.96 l)
Noise and Vibration	
Environmental noise (LwA)	100 dB
Whole-Body Vibration (ISO 2631-1)	0.96 m/s ²
Vibration to whole hand/arm	< 1.53 m/s ²



MID + LARGE FRAME



V210

Capacities	
Operating Capacity At 50% Tipping Load	2,100 lb (953 kg)
Operating Weight	7,480 lb (3393 kg)
Unladen weight	6,735 lb (3055 kg)
Tipping capacity	4,200 lb (1905 kg)
Weight and Dimensions	
Overall Operating Height - Fully Raised	160" (4054 mm)
Height to Hinge Pin - Fully Raised	121" (3061 mm)
Overall Height to top of ROPS	80" (2032 mm)
Dump angle at full height	42 °
Dump height	90" (2286 mm)
Overall length with bucket	139" (3543 mm)
Dump reach - Full height	34" (851 mm)
Rollback Angle at Full Height	92 °
Seat to ground height	37" (952.5 mm)
Overall width less bucket	64" (1623 mm)
Ground clearance	7" (178 mm)
Overall length - Less Bucket	108" (2743 mm)
Clearance Radius - Front with Bucket	84" (2146 mm)
Clearance Circle - Rear	66" (1664 mm)
Performances	
Travel Speed with Two-Speed - Maximum	12 mph (18.70 km/h)
Travel speed (unladen)	8 mph (12.10 km/h)
Engine	
Engine brand	Yanmar
Engine model	4TNV98C-NGL
Engine norm	Stage V
Gross Power (kW)	69.3 hp (51.7 kw)
Max. torque / Engine rotation	178 ft-lbs / 1625 rpm
Number of cylinders	4
Engine cooling system	Water
Battery voltage	12 V
Alternator - Ampere	100 A
Starter (kW)	3 kw
Hydraulics	
Standard flow - Auxiliary hydraulics	23 gpm (86.50 l/min)
Auxiliary Hydraulic Pressure	3475 PSI (239.59 bar)
High-Flow Auxiliary Hydraulics	30 gpm (114 l/min)
High-Flow Auxiliary Hydraulics Pressure	3325 PSI (229.25 bar)
Tank Capacities	
Fuel tank	28 gal (106 l)
Reservoir Capacity Hydraulics	6 gal (22.70 l)

V230

Capacities	
Operating Capacity At 50% Tipping Load	2,300 lb (1043 kg)
Operating Weight	7,750 lb (3515 kg)
Unladen weight	6,982 lb (3167 kg)
Tipping capacity	4,600 lb (2087 kg)
Weight and Dimensions	
Overall Operating Height - Fully Raised	161" (4079 mm)
Height to Hinge Pin - Fully Raised	122" (3099 mm)
Overall Height to top of ROPS	81" (2058 mm)
Dump angle at full height	42 °
Dump height	91" (2312 mm)
Overall length with bucket	141" (3589 mm)
Dump reach - Full height	33" (826 mm)
Rollback Angle at Full Height	92 °
Seat to ground height	39" (978 mm)
Overall width less bucket	67" (1707 mm)
Ground clearance	8" (203 mm)
Overall length - Less Bucket	110" (2789 mm)
Clearance Radius - Front with Bucket	85" (2171 mm)
Clearance Circle - Rear	66" (1689 mm)
Performances	
Travel Speed with Two-Speed - Maximum	12 mph (20 km/h)
Travel speed (unladen)	8 mph (12.70 km/h)
Engine	
Engine brand	Yanmar
Engine model	4TNV98CT-XNGL
Engine norm	Stage V
Gross Power (kW)	72 hp (53.7 kw)
Max. torque / Engine rotation	217 ft-lbs / 1800 rpm
Number of cylinders	4
Engine cooling system	Water
Battery voltage	12 V
Alternator - Ampere	100 A
Starter (kW)	3 kw
Hydraulics	
Standard flow - Auxiliary hydraulics	23 gpm (86.50 l/min)
Auxiliary Hydraulic Pressure	3475 PSI (239.59 bar)
High-Flow Auxiliary Hydraulics	30 gpm (114 l/min)
High-Flow Auxiliary Hydraulics Pressure	3325 PSI (229.25 bar)
Tank Capacities	
Fuel tank	28 gal (106 l)
Hydraulic Tank Capacity	6 gal (22.7 l)

V275

Capacities	
Operating Capacity At 50% Tipping Load	2,750 lb (1247 kg)
Operating Weight	8,200 lb (3719 kg)
Unladen weight	7,432 lb (3371 kg)
Tipping capacity	5,501 lb (2495 kg)
Weight and Dimensions	
Overall Operating Height - Fully Raised	167" (4252 mm)
Height to Hinge Pin - Fully Raised	129" (3277 mm)
Overall Height to top of ROPS	81" (2058 mm)
Dump angle at full height	42 °
Dump height	98" (2489 mm)
Overall length with bucket	150" (3810 mm)
Dump reach - Full height	33" (830 mm)
Rollback Angle at Full Height	92 °
Seat to ground height	39" (978 mm)
Overall width less bucket	67" (1712 mm)
Ground clearance	8" (209 mm)
Overall length - Less Bucket	119" (3023 mm)
Clearance Radius - Front with Bucket	90" (2289 mm)
Clearance Circle - Rear	72" (1829 mm)
Performances	
Travel Speed with Two-Speed - Maximum	11 mph (17.50 km/h)
Travel speed (unladen)	7 mph (11.40 km/h)
Engine	
Engine brand	Yanmar
Engine model	4TNV98CT-XNGL
Engine norm	Stage V
Gross Power (kW)	72 hp (53.7 kw)
Max. torque / Engine rotation	217 ft-lbs / 1800 rpm
Number of cylinders	4
Engine cooling system	Water
Battery voltage	12 V
Alternator - Ampere	100 A
Starter (kW)	3 kw
Hydraulics	
Standard flow - Auxiliary hydraulics	26 gpm (98.40 l/min)
Auxiliary Hydraulic Pressure	3475 PSI (239.59 bar)
High-Flow Auxiliary Hydraulics	33 gpm (126 l/min)
High-Flow Auxiliary Hydraulics Pressure	3325 PSI (229.25 bar)
Tank Capacities	
Fuel tank	28 gal (106 l)
Reservoir Capacity Hydraulics	6 gal (22.70 l)

V325

Capacities	
Operating Capacity at 50% Tipping Load	3,250 lb (1474 kg)
Rated Operating Capacity w/ Counterweight	3,450 lb (1565 kg)
Operating Weight	9,101 lb (4128 kg)
Tipping Capacity	6,499 lb (2948 kg)
Weight and Dimensions	
Overall Operating Height - Fully Raised	173" (4389 mm)
Height to Hinge Pin - Fully Raised	134" (3409 mm)
Overall Height to top of ROPS	82" (2084 mm)
Dump angle at Full Height	41°
Dump Height	104" (2634 mm)
Overall Length with Bucket	154" (3922 mm)
Dump Reach - Full Height	33" (846 mm)
Rollback Angle at Full Height	94°
Seat to Ground Height	41" (1039 mm)
Overall Width Less Bucket	73" (1852 mm)
Ground Clearance	8" (209 mm)
Overall Length - Less Bucket	123" (3124 mm)
Clearance Radius - Front with Bucket	91" (2299 mm)
Clearance Circle - Rear	75" (1905 mm)
Performances	
Travel Speed with Two-Speed - Maximum	7 mph (10.7 km/h)
Travel speed (unladen)	11 mph (17.3 km/h)
Wheels	
Standard tires	12 x 16.5
Engine	
Engine brand	Yanmar
Engine model	4TNV98C-NGL
Gross Power	72 hp (53.7 kw)
Max. Torque / Engine Rotation	217 ft-lbs / 1800 rpm
Starter	3 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	25 gpm (94.6 l/min)
Auxiliary Hydraulic Pressure	3450 PSI (238 bar)
High-Flow Auxiliary Hydraulics	34 gpm (129 l/min)
High-Flow Auxiliary Hydraulics Pressure	3325 PSI (229 bar)
Tank Capacities	
Fuel tank	28 gal (106 l)
Hydraulic Tank Capacity	7 gal (27 l)

V335

Capacities	
Operating Capacity at 50% Tipping Load	3,350 lb (1520 kg)
Rated Operating Capacity w/ Counterweight	3,550 lb (1610 kg)
Operating Weight	9,835 lb (4461 kg)
Tipping Capacity	6,702 lb (3040 kg)
Weight and Dimensions	
Overall Operating Height - Fully Raised	173" (4389 mm)
Height to Hinge Pin - Fully Raised	134" (3409 mm)
Overall Height to top of ROPS	82" (2084 mm)
Dump Angle at Full Height	41°
Dump Height	104" (2634 mm)
Overall Length with Bucket	154" (3922 mm)
Dump Reach - Full Height	33" (846 mm)
Rollback Angle at Full Height	94°
Seat to Ground Height	41" (1039 mm)
Overall Width Less Bucket	73" (1852 mm)
Ground Clearance	8" (209 mm)
Overall Length - Less Bucket	123" (3124 mm)
Clearance Radius - Front with Bucket	91" (2299 mm)
Clearance Circle - Rear	75" (1905 mm)
Performances	
Travel Speed with Two-Speed - Maximum	7 mph (10.7 km/h)
Travel speed (unladen)	12 mph (19.5 km/h)
Wheels	
Standard tires	12 x 16.5
Engine	
Engine brand	Deutz
Engine model	TCD3.6
Gross Power	99.8 hp (74.4 kw)
Max. Torque / Engine Rotation	302 ft-lbs / 1600 rpm
Starter	4 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	25 gpm (95 l/min)
Auxiliary Hydraulic Pressure	3450 PSI (238 bar)
High-Flow - Auxiliary hydraulics	40 gpm (151 l/min)
High-Flow Auxiliary Hydraulics Pressure	3450 PSI (238 bar)
Tank Capacities	
Fuel tank	28 gal (106 l)
Hydraulic Tank Capacity	7 gal (27 l)

V360

Capacities	
Operating Capacity at 50% Tipping Load	3,600 lb (1633 kg)
Rated Operating Capacity w/ Counterweight	3,800 lb (1724 kg)
Operating Weight	10,320 lb (4681 kg)
Tipping Capacity	7,200 lb (266 kg)
Weight and Dimensions	
Overall Operating Height - Fully Raised	175" (4435 mm)
Height to Hinge Pin - Fully Raised	136" (3454 mm)
Overall Height to top of ROPS	84" (2134 mm)
Dump Angle at Full Height	41°
Dump Height	105" (2678 mm)
Overall Length with Bucket	156" (3968 mm)
Dump Reach - Full Height	31" (798 mm)
Rollback Angle at Full Height	94°
Seat to Ground Height	43" (1085 mm)
Overall Width Less Bucket	75" (1916 mm)
Ground Clearance	10" (254 mm)
Overall Length - Less Bucket	125" (3173 mm)
Clearance Radius - Front with Bucket	93" (2350 mm)
Clearance Circle - Rear	76.5" (1943 mm)
Performances	
Travel Speed with Two-Speed - Maximum	7 mph (11.7 km/h)
Travel speed (unladen)	12 mph (20 km/h)
Wheels	
Standard tires	14 x 17.5 HD
Engine	
Engine brand	Deutz
Engine model	TCD3.6
Gross Power	114 hp (85 kw)
Max. Torque / Engine Rotation	339 ft-lbs / 1600 rpm
Starter	4 kW
Hydraulics	
Standard flow - Auxiliary hydraulics	25 gpm (95 l/min)
Auxiliary Hydraulic Pressure	3450 PSI (238 bar)
High-Flow - Auxiliary hydraulics	40 gpm (151 l/min)
High-Flow Auxiliary Hydraulics Pressure	3450 PSI (238 bar)
Tank Capacities	
Fuel tank	28 gal (106 l)
Hydraulic Tank Capacity	7 gal (27 l)

MAXIMIZE YOUR MACHINE



Scan with your phone to learn more and see a video overview.

EQUIPMENT TRACKING

Geolocation, geofencing, hours of use, etc. You are in charge of defining when and where your machine can be operated. If it is stolen or used without authorization, you are notified immediately. Location, alerts, fuel consumption at your fingertips. Knowing your machine better, you can optimize how it is used and driven, improving financial and logistics management. Save time and enjoy a greater peace of mind. See the myGEHL App section below.

PREDICTIVE ANALYTICS

By accessing machine data, our technicians can anticipate routine maintenance operations and repairs with the needed parts, meaning issues are resolved quicker. By anticipating the maintenance operations that need to be performed, ensuring your machine is serviced at the most suitable time. The risk of unexpected breakdowns and downtime are substantially reduced.

A TRUE PARTNER

With the network of GEHL partners by your side, you can work in complete confidence and count on high-level support and practical help at any moment. Monitoring of machine events enables you to implement corrective actions and optimize your up-time while also helping you understand your total cost of ownership. If the machine is sold, you can also pass on its "ID card" to the new owner as a gesture of transparency.

STAY CONNECTED NO MATTER WHERE YOU ARE



The myGEHL app allows for simpler day-to-day operations. Get machine information such as location, fuel and DEF levels, consumption data and more. Access documentation and videos for more information about your machine in real time. All at the tip of your fingers.



FULL SUPPORT

With over 160 years of experience in the field of handling equipment, our priority at GEHL is to keep your machine operating at maximum productivity. It's a mission realized through constantly refined services and innovations. Precision engineered spare parts. Qualified technicians, certified at our state-of-the-art training center. And advances like real-time equipment monitoring, at your fingertips. Maximize uptime and longevity with genuine Manitou Group parts, maintain productivity and enhance security with real-time monitoring and access control and enjoy ultimate peace of mind with extended protection coverage.

MANITOU GROUP ATTACHMENTS

MANITOU GROUP PARTS

MANITOU GROUP FINANCE

ALL NEW GEHL.COM



CHEK OUT THE NEW [GEHL.COM](https://www.gehl.com)

- SHOP MACHINES
- COMPARE MODELS
- FIND A DEALER
- LOCATE SUPPORT
- WORKING PHOTOS/VIDEOS

Also linked to our social media pages allowing you to join the conversation with other GEHL machine enthusiasts.



FROM YOUR COMPUTER
OR YOUR PHONE!

GEHL®

WORKS LIKE YOU™

GEHL.COM



Manitou Equipment America, LLC

P.O. Box 179



One GEHL Way



West Bend, WI, USA 53095



P: (262) 334-9461

F: (262) 338-7517

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.

© 2023 Manitou Equipment America, LLC. All registered and unregistered marks are owned by Manitou Equipment America, LLC or its affiliates. All rights reserved.

® denotes registration in the United States. Trademarks may or may not be registered in other countries.